


## 2-Line, Uni-directional, Transient Voltage Suppressor



### Features


- Stand-off voltage: 5V Max
- Transient protection for each line according to  
IEC61000-4-2(ESD):  $\pm 20\text{kV}$  (contact)  
IEC61000-4-5(surge): 5A (8/20 $\mu\text{s}$ )
- Low leakage current
- Ultra-low capacitance:  $C_J = 0.3\text{pF}$  typ
- Low clamping voltage
- RoHS Compliant

### Applications

- Cellular Handsets and Accessories
- Notebooks and Handhelds
- Personal Digital Assistants
- Portable Instrumentation
- Digital Cameras
- Peripherals
- Audio Players, Keypads, Side Keys, LCD
- USB 2.0


### Mechanical Data

- Package: SOT-143
- Case Material: "Green" Molding Compound
- Marking Information: See Below



R0502 = Device Marking Code  
Pin1 is ground

### Definitions of electrical characteristics





# ESDSL0502S1

## Maximum Ratings

PARAMETER	SYMBOL	LIMITS	UNIT
Peak pulse power ( $t_p = 8/20\mu s$ )	$P_{pk}$	75	W
Peak pulse current ( $t_p = 8/20\mu s$ )	$I_{pp}$	5	A
ESD according to IEC61000-4-2 air discharge	$V_{ESD}$	$\pm 25$	KV
ESD according to IEC61000-4-2 contact discharge		$\pm 20$	
Junction temperature	$T_J$	-55~125	$^{\circ}C$
Storage temperature	$T_{STG}$	-55~150	$^{\circ}C$

## Electrical Characteristics ( $T_a=25^{\circ}C$ Unless otherwise specified)

PARAMETER	Symbol	UNIT	Conditions	Min	Typ	Max
Reverse maximum working voltage	$V_{RWM}$	V				5
Reverse leakage current	$I_R$	$\mu A$	$V_{RWM} = 5V,$			0.5
Reverse breakdown voltage	$V_{(BR)}$	V	$I_T = 1mA,$	6		
Clamping voltage	$V_{CL}$	V	$I_{PP} = 1A, t_p = 8/20\mu s$			10
		V	$I_{PP} = 5A, t_p = 8/20\mu s$			15
Junction capacitance	CJ	pF	$V_R = 0V, f = 1MHz,$ between I/O pins		0.3	0.4
		pF	$V_R = 0V, f = 1MHz,$ any I/O pin to ground			0.8

Notes:

- (1). TLP parameter:  $Z_0 = 50\Omega, t_p = 100ns, t_r = 2ns,$  averaging window from 60ns to 80ns. RDYN is calculated from 4A to 16A.
- (2). Contact discharge mode, according to IEC61000-4-2.
- (3). Non-repetitive current pulse, according to IEC61000-4-5


## Ordering Information (Example)

PREFERED P/N	PACKING CODE	UNIT WEIGHT(mg)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
ESDSL0502S1	F1	Approximate 0.9	3000	30000	120000	7 reel




## ■ Characteristics (Typical)


8/20 $\mu$ s waveform per IEC61000-4-5




Clamping voltage vs. Peak pulse current




Non-repetitive peak pulse power vs. Pulse time




Contact discharge current waveform per IEC61000-4-2



Capacitance vs. Reverse voltage




Power derating vs. Ambient temperature








# ESDSL0502S1






## ■ Outline Dimensions



SYS YM	MILLIMETERS		
	MIN	NOM	MAX
A	0.90	-	1.15
A1	0.00	0.05	0.10
A2	0.90	-	1.05
b	0.30	0.40	0.50
b1	0.75	-	0.90
c	0.08	-	0.15
D	2.80	2.90	3.00
d	0.20 Typ		
E	1.20	1.30	1.40
E1	2.25	2.40	2.55
e	0.95 Typ		
e1	1.80	1.90	2.00
L	0.55 Ref		
L1	0.30	0.40	0.50
θ	0°	-	8°

## ■ Soldering Footprint



### Notes:

This recommended land pattern is for reference purposes only. Please consult your manufacturing group to ensure your PCB design guidelines are met



# ESDSL0502S1

---

## Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.